

**SECTION 1 – MATERIAL IDENTIFICATION AND USE****Material Name:** NATURAL GASOLINE (U.S.)**Use:** Process stream, fuels production**WHMIS Classification:** Class B, Div. 2; Class D, Div. 2, Sub-Div. A and B**Fire:** 4      **Reactivity:** 0      **Health:** 3**TDG:**      **UN:** 1267      **Class:** 3**Packing Group:** I (boiling point less than 35 deg. C)

II (boiling point 35 deg. C or above, and flash point less than 23 deg. C)

**Shipping Name:** PETROLEUM CRUDE OIL**Manufacturer/Supplier:** ENCANACORPORATION#1800, 855 - 2<sup>nd</sup> Street S.W., P.O. BOX 2850

CALGARY, ALBERTA, T2P 2S5

**Emergency Telephone:** (403) 645-3333**Chemical Family:** C5+ aliphatic and aromatic hydrocarbons.**SECTION 2 – HAZARDOUS INGREDIENTS OF MATERIAL**

<b>Hazardous Ingredients</b>	<b>Approximate Concentrations (%)</b>	<b>C.A.S. Nos.</b>	<b>LD50/LC50</b>	<b>Exposure Limits</b>
Pentanes	50-60	109-66-0	LC50, rat, 4 hr, 364 g/m <sup>3</sup>	600 ppm (OEL, TLV)
n-Hexane	35-50	110-54-3	LD50, rat, oral, 28.7 g/kg	50 ppm (OEL, TLV)
Butanes	<10	106-97-8	LC50, rat, 4 hrs, 658 g/m <sup>3</sup>	800 ppm (OEL) 1000 ppm (TLV <sup>1</sup> )
Benzene	0.1-1	71-43-2	LD50, rat, oral, 930 mg/kg LC50, rat, 4 hr, 13200 ppm	1 ppm (OEL) 0.5 ppm (TLV)

OEL = 8 hr. Alberta Occupational Exposure Limit; TLV = Threshold Limit Value (8 hrs)

<sup>1</sup> As Aliphatic hydrocarbon gases**SECTION 3 – PHYSICAL DATA FOR MATERIAL****Physical State:** Liquid**Specific Gravity:** 0.6 - 0.7**Vapour Density (air=1):** 2.5 - 3.0**Percent Volatiles, by volume:** 100**pH:** N.Av.**Coefficient of Water/Oil Distribution:** <0.1**Odour & Appearance:** colorless/straw coloured liquid, hydrocarbon odour

(N.Av. = not available    N.App. = not applicable)

**Vapour Pressure (mmHg):** 830 @ 20 deg. C.**Odour Threshold (ppm):** N.Av.**Evaporation Rate:** N.Av.**Boiling Pt. (deg.C):** 50**Freezing Pt. (deg.C):** -129 to -60**SECTION 4 – FIRE AND EXPLOSION****Flammability:** Yes      **Conditions:** Material will ignite at normal temperatures.**Means of Extinction:** Foam, CO<sub>2</sub>, dry chemical. Explosive accumulations can build up in areas of poor ventilation.**Special Procedures:** Use water spray to cool fire-exposed containers, and to disperse vapors if spill has not ignited. If safe, cut off fuel and allow flame to burn out.**Flash Point (deg.C) & Method:** <-40 (TCC)**Upper Explosive Limit (% by vol.):** 8**Lower Explosive Limit (% by vol.):** 1**Auto-Ignition Temp. (deg.C):** 260**Hazardous Combustion Products:** Carbon monoxide, carbon dioxide**Sensitivity to Impact:** No**Sensitivity to Static Discharge:** Yes, may ignite**TDG Flammability Classification:** 3

## SECTION 5 – REACTIVITY DATA

**Chemical Stability:** Yes                      **Conditions:** Heat  
**Incompatibility:** Yes                      **Substances:** Oxidizing agents (e.g. chlorine)  
**Reactivity:** Yes                              **Conditions:** Heat, strong sunlight  
**Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide

## SECTION 6 – TOXICOLOGICAL PROPERTIES OF PRODUCT

### Routes of Entry:

**Skin Absorption:** Yes                      **Skin Contact:** Yes (liquid)                      **Eye Contact:** Yes  
**Inhalation:** Acute: Yes                      **Chronic:** Yes                      **Ingestion:** Yes

**Effects of Acute Exposure:** Vapour may cause irritation of eyes, nose and throat, dizziness and drowsiness. Contact with skin may cause irritation and possibly dermatitis. Absorbed through intact skin. Contact of liquid with eyes may cause severe irritation.

**Effects of Chronic Exposure:** Due to presence of benzene and n-hexane, long term exposure may increase the risk of anaemia, leukemia and nervous system damage.

**Sensitization to Product:** N.Av.

**Exposure Limits of Product:** 0.5 ppm (TLV-TWA for benzene), 1 ppm (OEL for benzene)

**Irritancy:** Yes

**Synergistic Materials:** N.Av.

**Carcinogenicity:** Yes    **Reproductive Effects:** Possibly    **Teratogenicity:** Possibly    **Mutagenicity:** Possibly

## SECTION 7 – PREVENTIVE MEASURES

**Personal Protective Equipment:** Use positive pressure self-contained breathing apparatus, supplied air breathing apparatus or cartridge respirator approved for organic vapours where concentrations may exceed exposure limits.

**Gloves:** Viton (nitrile adequate for short exposure to liquid)    **Respiratory:** SCBA, SABA or cartridge respirator, depending on level of exposure.    **Eye:** Splash Goggles

**Footwear:** As per safety policy    **Clothing:** As per fire protection policy

**Engineering Controls:** Use only in well ventilated areas. Mechanical ventilation required in confined areas. Equipment must be explosion proof.

**Leaks & Spills:** Stop leak if safe to do so. Use personal protective equipment and respiratory protection. Use water spray to cool containers. Remove all ignition sources. Provide explosion-proof clearing ventilation, if possible. Prevent from entering confined spaces. Dyke and pump into containers for recycling or disposal. Notify appropriate regulatory authorities.

**Waste Disposal:** Contact appropriate regulatory authorities for disposal requirements.

**Handling Procedures & Equipment:** Avoid skin and eye contact with liquid. Avoid inhalation. Bond and ground all transfers. Avoid sparking conditions.

**Storage Requirements:** Store in a cool, dry, well ventilated area away from heat, strong sunlight, and ignition sources.

**Special Shipping Information:** N.Av.

## SECTION 8 – FIRST AID MEASURES

**Skin:** Flush skin with water, removing contaminated clothing. Get medical attention if irritation persists or large area of contact. Decontaminate clothing before re-use.

**Eye:** Immediately flush with large amounts of luke warm water for 15 minutes, lifting upper and lower lids at intervals. Seek medical attention if irritation persists.

**Inhalation:** Ensure own safety. Remove victim to fresh air. Give oxygen, artificial respiration, or CPR if needed. Seek medical attention immediately.

**Ingestion:** Give 2-3 glasses of milk or water to drink. DO NOT INDUCE VOMITING. Keep warm and at rest. Get immediate medical attention.

## SECTION 9 – PREPARATION DATE OF MSDS

Prepared By: EnCana Environment, Health and Safety (EHS)

Phone Number: (403) 645-2000    Preparation Date: July 10, 2008    Expiry Date: July 10, 2011